



HAF Series



Features

- High quality borosilicate glass tube
- Highly polished, one piece body
- Sturdy stainless steel flange connections
- Stainless steel float and guide rod
- Direct reading permanent scale
- Excellence in corrosion resistance

Specifications

- Max. operating pressure 0.8 Mpa
- Max. operating temperature ... 180 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration liquid water (S.G. 1)
- Accuracy of full scale flow $\pm 4\%$

Model	L/H	ANSI Flange Connector	Pressure (psi)
HAF-1	30~300	1/2"	110
HAF-2	60~600	1/2"	110
HAF-3	80~800	1/2"	110
HAF-4	90~900	3/4"	110
HAF-5	120~1200	3/4"	110
HAF-6	180~1800	3/4"	110
HAF-7	180~1800	1"	110
HAF-8	300~3000	1"	110
HAF-9	480~4800	1"	110
HAF-10	480~4800	1 1/4"	110
HAF-11	600~6000	1 1/4"	110
HAF-12	720~7200	1 1/4"	110
HAF-13	1~10 m ³ /h	1 1/2"	85
HAF-14	1.2~12 m ³ /h	1 1/2"	85
HAF-15	1.5~15 m ³ /h	1 1/2"	85
HAF-16	1.2~12 m ³ /h	2"	85
HAF-17	1.5~15 m ³ /h	2"	85
HAF-18	1.8~18 m ³ /h	2"	85
HAF-19	1.8~18 m ³ /h	2 1/2"	85
HAF-20	3~30 m ³ /h	2 1/2"	85
HAF-21	4~40 m ³ /h	2 1/2"	85
HAF-22	4~40 m ³ /h	3"	85
HAF-23	5~50 m ³ /h	3"	85
HAF-24	6~60 m ³ /h	3"	85
HAF-25	6~60 m ³ /h	4"	85
HAF-26	7~70 m ³ /h	4"	85
HAF-27	10~100 m ³ /h	4"	85

HYDOREX FLOW METER

RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com