



HFT Series



Features

- High quality borosilicate glass tube
- Highly polished, one piece body
- Sturdy connections
- Stainless steel float
- Direct reading permanent scale
- Excellence in corrosion resistance

Specifications

- Max. operating pressure 1.0Mpa
- Operating temperature ... 0° ~ 80°C
- Max. pressure drop ... less than 2 psi
- Calibration liquid water (S.G. 1)
- Accuracy of full scale flow ± 1.5%

Model	L / h (Liquid)	Connection	Pressure (Mpa)
HFT-1	2.5 ~ 25ml/min	1/4"	1.0
HFT-2	4 ~ 40ml/min	1/4"	1.0
HFT-3	6 ~ 60ml/min	1/4"	1.0
HFT-4	10 ~ 80ml/min	1/4"	1.0
HFT-5	10 ~ 100ml/min	1/4"	1.0
HFT-6	1 ~ 10	1/4"	1.0
HFT-7	1.6 ~ 16	1/4"	1.0
HFT-8	2.5 ~ 25	1/4"	1.0
HFT-9	4 ~ 40	1/4"	1.0
HFT-10	6 ~ 60	1/4"	1.0
HFT-11	10 ~ 100	1/2"	1.0
HFT-12	25 ~ 250	1/2"	1.0



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com