



HLG Series



Features

- High quality machined cast P.C. body
- Highly polished, one piece body
- Sturdy ABS connectors, Stainless Steel float
- Union ends simplify installation and maintenance
- Direct reading permanent scale

Specifications

- Max. operating pressure 85 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration media air
- Accuracy of full scale flow $\pm 5\%$

Model	m3/h (Air)	Connector NPT(M)	Pressure (psi)
HLG-1	1 ~ 7	1/2"	85
HLG-2	2 ~ 12	1/2"	85
HLG-3	3 ~ 30	1/2"	85
HLG-4	5 ~ 50	3/4"	85
HLG-5	7 ~ 70	3/4"	85
HLG-6	9 ~ 90	1"	85
HLG-7	15 ~ 150	1"	85
HLG-8	20 ~ 200	1"	85
HLG-9	35 ~ 300	2"	85
HLG-10	45 ~ 450	2"	85
HLG-11	150 ~ 700	2 1/2"	85
HLG-12	250 ~ 1200	2 1/2"	85
HLG-13	350 ~ 1500	2 1/2"	85

HYDOREX FLOW METER

RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com