



## HLV Series



### Features

- High quality machined cast PMMA body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale
- Adjustable flow control valve

### Specifications

- Max. operating pressure ..... 150 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration liquid ..... water (S.G. 1)
- Accuracy of full scale flow ....  $\pm 4\%$

Model	ml/min (liquid)	BSP Connector	Pressure (psi)
HLV-1	6 ~ 60	1/4" quick tube	150
HLV-2	8 ~ 80	1/4" quick tube	150
HLV-3	30 ~ 120	1/4" quick tube	150
HLV-4	40 ~ 400	1/4" quick tube	150
HLV-5	6 ~ 60	1/4"	150
HLV-6	10 ~ 70 GPH	1/4"	150
HLV-7	16 ~ 160	1/4"	150
HLV-8	25 ~ 250	1/4"	150
HLV-9	80 ~ 400	1/4"	150
HLV-10	100 ~ 500	1/4"	150
HLV-11	100 ~ 600	1/4"	150
HLV-12	200 ~ 800	1/4"	150
HLV-13	100 ~ 1000	1/4"	150
HLV-14	2.5 ~ 25 LPH	1/4"	150
HLV-15	5 ~ 45 LPH	1/4"	150
HLV-16	6 ~ 60 LPH	1/4"	150

HYDOREX FLOW METER

RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : [www.recalyx.com](http://www.recalyx.com)

email : [sales@recalyx.com](mailto:sales@recalyx.com)