



HPG Series



Features

High quality machined cast PMMA body
 Highly polished, one piece body
 Sturdy PVC connectors, Stainless Steel float
 Direct reading permanent scale

Specifications

Max. operating pressure 150 psi
 Max. operating temperature ... 50 degree C @ 0 psi
 Max. pressure drop ... less than 2 psi
 Calibration media air
 Accuracy of full scale flow ± 4%

Model	Nm ³ /hr (Air)	BSPT (M) Connector	Pressure (psi)
HPG-1	0.01 ~ 0.1	1/2"	150
HPG-2	0.04 ~ 0.4	1/2"	150
HPG-3	0.1 ~ 1	1/2"	150
HPG-4	0.16 ~ 1.6	1/2"	150
HPG-5	0.24 ~ 3	1/2"	150
HPG-6	0.4 ~ 4	1/2"	150
HPG-7	0.6 ~ 6	1/2"	150
HPG-8	0.8 ~ 8	1/2"	150
HPG-9	1 ~ 10	1/2"	150
HPG-10	1.6 ~ 16	1/2"	150
HPG-11	2 ~ 20	1/2"	150
HPG-12	2.5 ~ 25	1/2"	150
HPG-13	3 ~ 30	1/2"	150
HPG-14	4 ~ 40	1/2"	150
HPG-15	6 ~ 60	1"	150
HPG-16	10 ~ 100	1"	150
HPG-17	16 ~ 160	1"	150
HPG-18	20 ~ 200	1"	150
HPG-19	25 ~ 250	1"	150
HPG-20	30 ~ 300	1"	150
HPG-21	35 ~ 350	1"	150

HYDOREX FLOW METER

RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com