



## HPGV Series



### Features

- High quality machined cast PMMA body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale
- Come with adjustable flow control valve

### Specifications

- Max. operating pressure ..... 150 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration media ..... air
- Accuracy of full scale flow ....  $\pm 4\%$

Model	Nm <sup>3</sup> /hr (Air)	BSPT (M) Connector	Pressure (psi)
HPGV-1	0.1 ~ 1	1/2"	150
HPGV-2	0.16 ~ 1.2	1/2"	150
HPGV-3	0.3 ~ 3	1/2"	150
HPGV-4	1.4 ~ 4	1/2"	150
HPGV-5	0.6 ~ 6	1/2"	150
HPGV-6	1 ~ 10	1/2"	150
HPGV-7	1.6 ~ 16	1/2"	150
HPGV-8	2.5 ~ 25	1/2"	150
HPGV-9	4 ~ 40	1/2"	150
HPGV-10	20 ~ 100	1"	150
HPGV-11	40 ~ 160	1"	150
HPGV-12	50 ~ 250	1"	150

HYDOREX FLOW METER

RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : [www.recalyx.com](http://www.recalyx.com)

email : [sales@recalyx.com](mailto:sales@recalyx.com)