




HPZG Series



Features

- High quality machined cast acrylic body
- Highly polished, one piece body
- Sturdy PVC connectors, Stainless Steel float
- Direct reading permanent scale

Specifications

- Max. operating pressure 150 psi
- Max. operating temperature ... 50 degree C @ 0 psi
- Max. pressure drop ... less than 2 psi
- Calibration media air
- Accuracy of full scale flow $\pm 4\%$

Model	Nm ³ /hr (Air)	BSP Connector	Pressure (psi)
HPZG-1	0.8 ~ 8	1/2"(F)	150
HPZG-2	1 ~ 10	1/2"(F)	150
HPZG-3	1.6 ~ 16	1/2"(F)	150
HPZG-4	2.5 ~ 25	1/2"(F)	150
HPZG-5	4 ~ 40	1/2"(F)	150
HPZG-6	6 ~ 60	3/4"(F)	150
HPZG-7	10 ~ 100	1 1/2"(M)	150
HPZG-8	15 ~ 140	1 1/2"(M)	150
HPZG-9	16 ~ 160	1 1/2"(M)	150
HPZG-10	25 ~ 250	1 1/2"(M)	150
HPZG-11	35 ~ 350	1 1/2"(M)	150
HPZG-12	80 ~ 400	1 1/2"(M)	150
HPZG-13	100 ~ 500	2"(M)	150
HPZG-14	120 ~ 600	2"(M)	150
HPZG-15	300 ~ 850	2"(M)	150
HPZG-16	400 ~ 1200	2"(M)	150
HPZG-17	500 ~ 1400	2"(M)	150



RECALYX INDUSTRIES (M) SDN BHD (532841-W)

No. 40, Jalan Taming 6, Taming Jaya Industrial Park, 43300 Balakong, Selangor, Malaysia.

Tel : +6 03-8961 2168

Fax : +6 03-8961 0168

URL : www.recalyx.com

email : sales@recalyx.com