



SPECIFICATION

Material	: 304 SS, 316L SS, Carbon Steel With Inner Rubber Lining
Finishing	: Mirror Polished, Sand Blast
Inlet / Outlet	: 4" to, 12" Flange
Vent	: 1/4" NPT (F), 3/4" (F)
Design pressure	: 185 psi
Max. Operating pressure	: 150 psi
Design temperature	: 50 to 200 Degree C



MODEL	CARTRIDGES	INLET/ OUTLET	(M ³ /HR)
HFH-40	1 x 20"	4"	40
HFH-80	1 x 40"	4"	80
HFH-120	1 x 60"	4"	120
HFH-240	2 x 60"	6"	240
HFH-360	3 x 60"	6"	360
HFH-480	4 x 60"	6"	480
HFH-600	5 x 60"	6"	600
HFH-720	6 x 60"	6"	720
HFH-840	7 x 60"	6"	840
HFH-960	8 x 60"	6"	960
HFH-1080	9 x 60"	6"	1080
HFH-1200	10 x 60"	6"	1200
HFH-1320	11 x 60"	6"	1320

MODEL	CARTRIDGES	INLET/ OUTLET	(M ³ /HR)
HFH-1440	12 x 60"	6"	1440
HFH-1560	13 x 60"	8"	1560
HFH-1680	14 x 60"	8"	1680
HFH-1800	15 x 60"	8"	1800
HFH-1920	16 x 60"	10"	1920
HFH-2040	17 x 60"	10"	2040
HFH-2160	18 x 60"	10"	2160
HFH-2280	19 x 60"	10"	2280
HFH-2400	20 x 60"	10"	2400
HFH-2520	21 x 60"	12"	2520
HFH-2640	22 x 60"	12"	2640
HFH-2760	23 x 60"	12"	2760
HFH-2880	24 x 60"	12"	2880